


TecsPak® Mini Bumper Spec Sheet



| Bumper | Free Height in. | Free Bulge in. | Wrench Opening in. | Base Diameter in. | Mounting Hole in. | Solid Height in. | Bulge @ Solid Ht. in. | Rated Energy Capacity In-lbs. | Peak Dynamic Force Lbs. | Shipping Weight oz. | Recommended Mounting Bolt |
|---------|-----------------|----------------|--------------------|-------------------|-------------------|------------------|-----------------------|-------------------------------|-------------------------|---------------------|---------------------------|
| GBA-98S | .58 ± .01 | .54 ± .015 | .34 ± .015 | .51 ± .01 | .18 ± .01 | .29 ± .005 | .76 ± .01 | 18 | 105 | 0.05 | M4X0.7 SHCS |
| GBA-99S | .73 ± .01 | .68 ± .015 | .42 ± .015 | .64 ± .01 | .21 ± .01 | .40 ± .005 | .96 ± .01 | 33 | 290 | 0.10 | M5X0.8 SHCS |
| GBA-A | .43 ± .01 | .47 ± .015 | .23 ± .015 | .41 ± .01 | .14 ± .01 | .24 ± .005 | .60 ± .01 | 20 | 180 | 0.03 | M3X0.5 SHCS |
| GBA-C | .62 ± .01 | .67 ± .015 | .33 ± .015 | .58 ± .01 | .17 ± .02 | .39 ± .005 | .82 ± .01 | 50 | 350 | 0.13 | M4X0.7 SHCS |
| GBA-E | .74 ± .01 | .79 ± .015 | .40 ± .015 | .70 ± .01 | .21 ± .01 | .39 ± .005 | 1.01 ± .01 | 90 | 500 | 0.14 | M5X0.8 SHCS |